


ULTIMA® High-NRC

Lay-in & Tegular
fine texture





Ultima High-NRC Beveled Tegular with Suprafine® 9/16" suspension system (Pg. 266)

KEY SELECTION ATTRIBUTES

- Smooth, clean, durable finish – Washable, Impact-resistant, Scratch-resistant, Soil-resistant
- 88% Biobased content (see page 331)
- Excellent combination of acoustical performance; Articulation Class (170), NRC (0.80), and CAC (35)
- Ceiling-2-Ceiling™ post-consumer recycled content options: item 1942HRC. 53% pre-consumer, 15% post-consumer
- Non-directional visual reduces installation time and scrap
- 30-Year Limited System Warranty against visible sag, mold/mildew, and bacterial growth

TYPICAL APPLICATIONS

- Open plan offices
- Healthcare – assists in addressing HIPAA and FGI acoustical requirements
- Classrooms
- Corridors
- Lobbies/reception areas
- Department stores/retail
- Open plenum areas (in acoustical clouds; e.g., Formations™)



Visit Armstrong.com
Photo Gallery to view more
installation photos


SEARCH: ultima

DETAIL (Other Suspension Systems compatible. Refer to listing on page 230.)



1. Ultima High-NRC Lay-in
2. Ultima High-NRC Beveled Tegular
3. Ultima High-NRC with Suprafine 9/16" suspension system
4. Ultima High-NRC with Silhouette® XL® 9/16" 1/4" Reveal
5. Ultima High-NRC with Interlude® XL suspension system

COLOR



White

ULTIMA® High-NRC

Lay-in & Tegular

fine texture

HRC items contain 15% or greater post-consumer recycled ceilings



UP TO **68%** RECYCLED CONTENT

LEED®



Calculate LEED contribution at armstrong.com/greengenie

*LOCATION DEPENDENT



VISUAL SELECTION


PERFORMANCE

Dots represent high level of performance.

Edge Profile	Susp. Dwg. Pgs. 273-277 armstrong.com/catdwgs	Item No.	Dimensions (Inches)	Acoustics		Fire Rating	Light Reflect	Anti-Mold & Mildew	Sag Resist	Certified Low VOC Emissions	Durability				Recycled Content*	Recycle Program	Warranty†
				NRC	CAC						AC	Wash	Impact	Scratch			
ULTIMA High-NRC Square Lay-in																	
15/16" Square Lay-in	1	NEW 1940	24 x 24 x 1"	0.80	35	170	Class A	0.87	•	•	•	•	•	•	•	•	30
	1	NEW 1943	24 x 48 x 1"	0.80	35	170	Class A	0.87	•	•	•	•	•	•	•	•	30
	1	Other Sizes	W: 12" - 24" / L: 24" - 60" 1" Thick	0.80	35	170	Class A	0.87	•	•	•	•	•	•	•	•	30
ULTIMA High-NRC Beveled Tegular																	
15/16" Beveled Tegular	15	1941	24 x 24 x 1"	0.80	35	170	Class A	0.87	•	•	•	•	•	•	•	•	30
	15	1944	24 x 48 x 1"	0.80	35	170	Class A	0.87	•	•	•	•	•	•	•	•	30
	15	Other Sizes	W: 12" - 24" / L: 24" - 60" 1" Thick	0.80	35	170	Class A	0.87	•	•	•	•	•	•	•	•	30
9/16" Beveled Tegular	29, 44, 48, 52, 56, 60	1942	24 x 24 x 1"	0.80	35	170	Class A	0.87	•	•	•	•	•	•	•	•	30
	29, 44, 48, 52, 56, 60	1942HRC**	24 x 24 x 3/4"	0.75	35	170	Class A	0.87	•	•	•	•	•	•	•	•	30
	29, 44, 48, 52, 56, 60	1945	24 x 48 x 1"	0.80	35	170	Class A	0.87	•	•	•	•	•	•	•	•	30
	29, 44, 48, 52, 56, 60	Other Sizes	W: 12" - 24" / L: 24" - 48" 1" Thick	0.80	35	170	Class A	0.87	•	•	•	•	•	•	•	•	30

** Other sizes not available for HRC items.

SUSPENSION SYSTEMS



Items 1942, 1945 – CAC 33 on Interlude, Sonata, Suprafine

PHYSICAL DATA

Material
Wet-formed mineral fiber with DuraBrite® acoustically transparent membrane

Surface Finish
DuraBrite with factory-applied latex paint

Fire Performance
ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less. (UL labeled)

ASTM E1264 Classification
Type IV, Form 2, Pattern E
Fire Class A

Sag Resistance
HumiGuard® Plus – superior resistance to sagging in high humidity conditions up to, but not including, standing water and outdoor applications.

Anti-Mold/Mildew & Bacteria
BioBlock® Plus contains an anti-microbial treatment and provides guaranteed resistance against growth of mold/mildew and Gram-positive and Gram-negative odor/stain-causing bacteria for 30 years.

VOC Emissions
Third party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.1, 2010. This standard is the guideline for low emissions in LEED, CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

High Recycled Content*
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

Insulation Value
R Factor – 2.2 (BTU units)
R Factor – 0.39 (Watts units)

30-Year Performance Guarantee & Warranty†
When installed with Armstrong Suspension System. Details at armstrong.com/warranty

Weight; Square Feet/Carton
1940, 1941, 1942 – 1.125 lbs/SF; 40 SF/ctn
1942HRC, 1943, 1944, 1945 – 1.125 lbs/SF; 48 SF/ctn

Minimum Order Quantity
1 carton, excludes other sizes

Metric Items Available
1940M, 1943M, 1941M, 1944M, 1942M, 1945M – Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.



TechLineSM / 1 877 ARMSTRONG
armstrong.com/commcellings
(search: ultima)
BPCS-3570-614

LEED® is a registered trademark of the U.S. Green Building Council
All other trademarks used herein are the property of AWI Licensing Company and/or its affiliates © 2013 AWI Licensing Company
Printed in the United States of America

