

PEBBLE™
Square Lay-in
medium texture



Pebble with Prelude® 15/16" suspension system (Pg. 259)


KEY SELECTION ATTRIBUTES

- Excellent acoustical absorption (perforated items)
- Easy-clean, durable surface
- Economical
- 30-Year Limited System Warranty against visible sag, mold/mildew, and bacterial growth

TYPICAL APPLICATIONS

- Discount/grocery stores
- Locker rooms
- Utility rooms
- Lavatories/restrooms

DETAIL



1. Pebble
2. Pebble with Prelude 15/16" suspension system

COLOR



PEBBLE™

Square Lay-in medium texture

UP TO **71%** RECYCLED CONTENT

LEED®

- acoustics
- energy
- daylight & views
- indoor air quality
- renewable materials
- recycled content
- waste mgmt
- local* materials

Calculate LEED contribution at armstrong.com/greengenie

*LOCATION DEPENDENT




VISUAL SELECTION

PERFORMANCE

Dots represent high level of performance.

Edge Profile	Susp. Dwg. Pgs. 273-277 armstrong.com/catdwgs	Item No.	Dimensions (Inches)	Acoustics		Fire Rating	Light Reflect	Anti-Mold & Mildew	Sag Resist	Certified Low VOC Emissions	Durability					Recycled Content*	Recycle Program	Warranty†
				NRC	CAC						Water Repel	Wash	Scrub	Impact	Soil			
PEBBLE Square Lay-in (Perforated)																		
15/16" Square Lay-in	1	2983	24 x 48 x 5/8"	0.70	N/A	Class A	0.89	•	•	–	•	•	•	•	•	High	–	30
	1	2970	24 x 60 x 5/8"	0.70	N/A	Class A	0.89	•	•	–	•	•	•	•	•	High	–	30
	1	Other Sizes	W: 12" - 30" / L: 12" - 60" 5/8" Thick	0.70	N/A	Class A	0.89	•	•	–	•	•	•	•	•	High	–	30
PEBBLE High-NRC (Perforated)																		
15/16" Square Tegal	1	2988	24 x 24 x 1"	0.80	N/A	Class A	0.89	•	•	–	•	•	•	•	•	High	–	30
	1	2989	24 x 48 x 1"	0.80	N/A	Class A	0.89	•	•	–	•	•	•	•	•	High	–	30
	1	Other Sizes	W: 12" - 30" / L: 12" - 60" 1" Thick	0.80	N/A	Class A	0.89	•	•	–	•	•	•	•	•	High	–	30
PEBBLE (Unperforated)																		
15/16" Square Tegal	1	2968	24 x 48 x 5/8"	0.50	N/A	Class A	0.89	•	•	–	•	•	•	•	•	High	–	30
	1	Other Sizes	W: 12" - 30" / L: 12" - 60" 5/8" Thick	0.50	N/A	Class A	0.89	•	•	–	•	•	•	•	•	High	–	30

SUSPENSION SYSTEMS



PHYSICAL DATA

Material
Fiberglass with vinyl facing

Surface Finish
Scrubable vinyl film facing (UV protected)

Fire Performance
ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less. (UL labeled)

ASTM E1264 Classification
Type XII, Form 1, Pattern E C
Fire Class A

Sag Resistance
HumiGuard® Plus – superior resistance to sagging in high humidity conditions up to, but not including, standing water and outdoor applications.

Anti Mold/Mildew & Bacteria
Fiberglass substrate is inherently resistant to the growth of mold, mildew, and bacteria.

High Recycled Content*
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

Acoustical Details
A CAC value of 37 can be achieved by backloading fiberglass products with Item 769 or 770.

Insulation Value
2968, 2970, 2983 - R Factor - 2.6 (BTU units)
R Factor - 0.46 (Watts units)
2988, 2989 - R Factor - 4.0 (BTU units)
R Factor - 0.70 (Watts units)

30-Year Performance Guarantee & Warranty†
When installed with Armstrong Suspension System. Details at armstrong.com/warranty

Weight; Square Feet/Carton
2968, 2983 – 0.20 lbs/SF; 128 SF/ctn
2970 – 0.20 lbs/SF; 120 SF/ctn
2988, 2989 – 0.31 lbs/SF; 80 SF/ctn

Minimum Order Quantity
1 carton, excludes special sizes

Metric Items Available
2983M, 2970M, 2988M, 2989M, 2968M – Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.



TechLine™ / 1 877 ARMSTRONG
armstrong.com/commceilings
(search: pebble)
BPCS-3052-413

LEED® is a registered trademark of the U.S. Green Building Council
All other trademarks used herein are the property of AWI Licensing Company and/or its affiliates © 2013 AWI Licensing Company
Printed in the United States of America

