

# TINCRAFT™

## Circles, Squares™ & Triangles™

### Tegular

smooth texture



TinCraft Squares with Suprafine® 9/16" suspension system (Pg. 266)



TinCraft Circles with Faux Coat Bronze and coordinated Prelude® 15/16" suspension system (Pg. 259)



#### KEY SELECTION ATTRIBUTES

- Early 20th century embossed metal look
- Affordable, practical alternative to traditional tin and metal ceilings
- Finely detailed design for upscale look

#### TYPICAL APPLICATIONS

- Specialty shops/stores
  - Restaurants
  - Dining areas
- \* Not recommended for areas requiring acoustical performance

#### COLOR SELECTION

Due to printing limitations, shade may vary from actual product.



White (WH)



Faux Coat Pewter (PW)



Faux Coat Bronze (BZ)



Silver (SL)





Copper (CP)

Color finishes available on TinCraft Circles only. Colored ceilings are dye-lotted and should be segregated by dye lot. Do not mix.

#### DETAIL

(Other Suspension Systems compatible. Refer to listing on page 220.)



1. TinCraft Circles
2. TinCraft Squares
3. TinCraft Triangles
4. TinCraft Circles with Prelude 15/16" suspension system
5. TinCraft Squares with Suprafine 9/16" suspension system
6. TinCraft Triangles with Suprafine 9/16" suspension system

# TINCRAFT™

## Circles, Squares™ & Triangles™

Tegular  
smooth texture

UP TO **55%** RECYCLED CONTENT

**LEED®**

- acoustics
- energy
- daylight & views
- indoor air quality
- renewable materials
- recycled content
- waste mgmt
- local\* materials

Calculate LEED contribution at [armstrong.com/greengenie](http://armstrong.com/greengenie)

\*LOCATION DEPENDENT



### VISUAL SELECTION

### PERFORMANCE

Dots represent high level of performance.

Edge Profile	Susp. Dwg. Pgs. 273-277 <a href="http://armstrong.com/catdwgs">armstrong.com/catdwgs</a>	Item No.	Dimensions (Inches)	Acoustics		Fire Rating	Light Reflect (White only)	Anti-Mold & Mildew	Sag Resist	Certified Low VOC Emissions	Durability	Recycled Content*	Recycle Program	Warranty†
				NRC	CAC									
<b>TINCRAFT Circles</b>				UL Classified										
15/16" Flush Tegular	3	<b>8008</b> _ _ ♦♦	24 x 24 x 3/4" □	N/A	35	Class A	0.78	–	Std	•	Std	Std	•	1
<b>TINCRAFT Squares</b>														
9/16" Flush Tegular	3	<b>8009</b>	24 x 24 x 3/4" □	N/A	35	Class A	0.78	–	Std	•	Std	High	•	1
<b>TINCRAFT Triangles</b>														
9/16" Flush Tegular	3	<b>8010</b>	24 x 24 x 3/4" □	N/A	35	Class A	0.78	–	Std	•	Std	High	•	1

♦♦ Add 2-letter color suffix to item number when specifying or ordering (e.g., 8008 P W).



Circles



Squares




Triangles

### SUSPENSION SYSTEMS

For coordinating color, specify Prelude® XL® items 7301 main beam, XL7342, XL7328 cross tees, and 7800 wall molding with the appropriate 2-letter color suffix.

15/16"



Prelude

9/16"



Suprafine®

### PHYSICAL DATA

#### Material

Wet-formed mineral fiber

#### Surface Finish

Factory-applied latex paint

#### Fire Performance

ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less. (UL labeled)

#### ASTM E1264 Classification

Type III, Form 2, Pattern J Z (Classic embossed tin ceiling design)  
Fire Class A

#### VOC Emissions

Third party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.1, 2010. This standard is now referenced as the guideline for low emissions in LEED, CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

#### High Recycled Content\*

Classified as containing greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

#### Insulation Value

Average R – 1.6 (BTU units)  
Average R – 0.28 (Watts units)

#### 30-Year Performance Guarantee & Warranty†

When installed with Armstrong Suspension System. Details at [armstrong.com/warranty](http://armstrong.com/warranty)

#### Weight; Square Feet/Carton

8008 – 0.90 lbs/SF; 48 SF/ctn  
8009, 8010 – 1.23 lbs/SF; 32 SF/ctn

#### Minimum Order Quantity

1 carton



TechLine<sup>SM</sup> / 1 877 ARMSTRONG  
[armstrong.com/commceilings](http://armstrong.com/commceilings)  
(search: tincraft)  
BPCS-3690-813

LEED® is a registered trademark of the U.S. Green Building Council  
All other trademarks used herein are the property of AWI Licensing Company and/or its affiliates © 2013 AWI Licensing Company  
Printed in the United States of America



220

MINERAL FIBER

